```
    {
      "key" : "Mike McGrath",
      "doc_count" : 2
    },
    {
      "key" : "Terry Norton",
      "doc_count" : 2
    },
    {
      "key" : "Adam Scott",
      "doc_count" : 1
    }
..
]}
```

Each bucket represents an author with the number of books the author wrote. By default, the `terms` aggregation only returns the top 10 aggregations, but we can tweak this return size by setting the `size` parameter, as the following listing shows.

Listing 13.17 A `terms` query with a custom size

```
GET books/_search?size=0
{
  "aggs": {
    "author_book_count": {
      "terms": {
        "field": "author.keyword",
        "size": 25
      }
    }
  }
}
```

Sets the aggregation size

Here, setting `size` to `25` fetches 25 aggregations (25 authors and their book counts).

13.3.5 The multi-terms aggregation

The `multi_terms` aggregation resembles the `terms` aggregation with an additional feature: it aggregates data based on multiple keys. For example, rather than just finding the number of books written by an author, we can find the number of books with a specific title and author. The following listing gets the author and their book's title(s) as a map.

Listing 13.18 Aggregation for authors and their book titles as a map

```
GET books/_search?size=0
{
  "aggs": {
    "author_title_map": {
      "multi_terms": {
        "terms": [
          {
```

Declares the aggregation type

The set of terms with which to form the author/title map