Figure 13.8 shows the parent aggregation `cappuccino_sales`. The pipeline aggregation `cumulative_sum`, as defined by `total_cappuccinos`, refers to the parent aggregation via `buckets_path`, which is set with a value referring to the name of the parent aggregation.

```
GET coffee_sales/_search
{
  "size": 0,
  "aggs": {
    "sales_by_coffee": {
      "date_histogram": {...},
      "aggs": {
        "cappuccino_sales": {
          "sum": {...}
        },
        "total_cappuccinos": {
          "cumulative_sum": {
            "buckets_path": "cappuccino_sales"
          }
        }
      }
    }
  }
}
```

The `cumulative_sum` refers to the parent aggregation (defined by `cappuccino_sales`) by setting `buckets_path` to `cappuccino_sales`

Figure 13.8 Parent pipeline aggregation `buckets_path` setting

The `buckets_path` setting becomes a bit more involved if the aggregation in play is a sibling aggregation. The `max_bucket` in the aggregation in figure 13.9 is a sibling pipeline aggregation (defined under the `highest_cappuccino_sales_bucket`

```
GET coffee_sales/_search
{...}

GET coffee_sales/_search
{
  "size": 0,
  "aggs": {
    "sales_by_coffee": {
      "date_histogram": {...},
      "aggs": {
        "cappuccino_sales": {...}
      }
    },
    "highest_cappuccino_sales_bucket":{
      "max_bucket": {
        "buckets_path": "sales_by_coffee>cappuccino_sales"
      }
    }
  }
}
```

Sibling aggregations

The `max_bucket` (a sibling aggregation) refers to the constituents of sibling aggregations (defined by `sales_by_coffee` and `cappuccino_sales`) by setting `buckets_path` to `sales_by_coffee>cappuccino_sales`.

The "`>`" operator is the aggregation separator.

The `buckets_path` for a sibling pipeline aggregation

Figure 13.9 Sibling pipeline aggregation `buckets_path` setting