FETCHING SELECTED FIELDS

We can fetch just a few selected fields rather than the entire document. Elasticsearch provides a `fields` object to indicate which fields should be returned. We define the fields explicitly in this object. For example, the following query fetches only the `title` and `rating` fields in the response:

```
GET movies/_search
{
  "_source": false,
  "query": {
    "match": {
      "certificate": "R"
    }
  },
  "fields": [
    "title",
    "rating"
  ]
}
```

The following snippet shows the response. The document is resorted with the `title` and `rating` fields, as expected:

```
{
  "_index" : "movies",
  "_type" : "_doc",
  "_id" : "1",
  "_score" : 0.58394784,
  "fields" : {
    "rating" : [
      9.296875
    ],
    "title" : [
      "The Shawshank Redemption"
    ]
  }
}
```

Note that each field is returned as an array instead of a single field. Because it could potentially have multiple values, the results are represented as a json array (Elasticsearch doesn't have an array type).

We can also use wildcards in the field's mapping. For example, setting `title*` retrieves `title`, `title.original`, `title_long_descripion`, `title_code`, and any other fields with the `title` prefix. (We do not have all these fields in our mapping, other than `title` and `title.original`, so you can add them to the mapping to experiment with the wildcard setting.)

SCRIPTED FIELDS

Sometimes we need to compute a field on the fly and add it to the response. For example, suppose we want to set a movie as top-rated if it falls within the range of the