```
            "lat": 49,
            "lon": 0.2
          }
        }
      }
    }
  }
```

This query searches for cafes in a given georectangle constructed with `top_left` and `bottom_right` parameters. Here, we use the `cafes` index in the URL (`GET`) when invoking the `geo_bounding_box` query. Other than swapping the geopoints index (`restaurants`) with an index consisting of geoshapes (`cafes`), there's no difference in the query!

We provide the longitude and latitude values as objects in listing 12.6. However, latitude and longitude can be set with multiple formats: as an array or WKT values. For example, the earlier `geo_bounding_box` queries provided `top_left` and `bottom_right` attributes as `"lat"` and `"lon"` objects:

```
"top_left": {
  "lat": 52.00,
  "lon": 0.20
}
```

Instead, we can set longitude and latitude as an array. But here's one gotcha to consider: the values in the array *must be reversed*. They should be `lon` and then `lat` (as opposed to `lat` and then `lon` in the previous examples).

NOTE For more information on this `lon-lat` inconsistency in geospatial software modules, see the article by Tom MacWright at https://macwright.com/lonlat.

The following listing shows the same `geo_bounding_box` query, but this time with longitude and latitude (highlighted in bold) provided as an array.

Listing 12.7 Geoquery with a geopoint specified as an array

```
GET restaurants/_search
{
  "query": {
    "bool": {
      "must": [
        {
          "match_all": {}
        }
      ],
      "filter": [
        {
          "geo_bounding_box": {
            "location": {
              "top_left": [0, 52.00],
```

The top_left attribute with lon and lat values