```
            "bottom_right": [0.10, 49]
          }
        }
      }
    ]
  }
 }
}
```

The bottom_right attribute with lon and lat values

We define the `top_left` and `bottom_right` attributes as an array of two geopoints: longitude and latitude.

We can also provide the longitude and latitude as a vector object. WKT is a standard text markup language for representing vector objects on a map. For example, to represent a point in WKT, we write `POINT(10, 20)`, which represents a point on a map with x- and y-coordinates 10 and 20, respectively. Elasticsearch provides WKT markup for bounding-box queries as `BBOX` with the respective values. The following query shows this.

Listing 12.8 Geoquery with a location represented as WKT

```
GET restaurants/_search
{
  "query": {
    "bool": {
      "must": [
        {
          "match_all": {}
        }
      ],
      "filter": [
        {
          "geo_bounding_box": {
            "location": {
              "wkt":"BBOX(0.08, 0.04, 52.00, 49.00)"
            }
          }
        }
      ]
    }
  }
}
```

Sets the coordinates in WKT format

The `geo_bounding_box` filter's `location` field accepts the coordinates as `BBOX` with the corresponding longitude and latitude values. `BBOX` creates a georectangle from the pair to make the top-left and bottom-right points.

Other than your own preference, there's no difference between the WKT and array formats. If you are building an application that uses WKT standards for geodata, it makes sense to use WKT-based indexing and searching in Elasticsearch.

In this section, we learned how to find locations inside a georectangle using the `geo_bounding_box` query. Sometimes we may want to find restaurants near a central location: say, all restaurants 10 km from the city's center. This is where we can employ