In a `multi_match` query, we can bump up (boost) the criteria for a specific field. Suppose that when searching for "C# Guide", we decide that finding the word in the title is more important than finding it in tags. In this case, we can boost the field's importance field by using a caret and a number: `title^2`, for example. The following listing shows the full query for this scenario.

Listing 10.19 Boosting the score for a field in a `multi_match` query

```
GET books/_search
{
  "query": {
    "multi_match": {
      "query": "C# Guide",
      "fields": ["title^2", "tags"]
    }
  }
}
```

Doubles the importance of the title field

In this listing, we double the `title` field's importance. So if the text "C# Guide" is found in the `title` field, that document has a higher score than a document with the text in the `tags` field.

Next, let's look at the `query_string` query. This type of query helps us build a request URL search, mimicking Kibana Query Language (KQL) in a Query DSL format. We review the need for the `query_string` query and work with it in the following section.

Query strings and KQL

In chapter 8, we looked at the URI search method (a search query approach in addition to Query DSL). We created a request by passing the `search` query and its parameters to the URL, rather than in a request body. We also saw that although the URI method is simple, it becomes error-prone as the complexity of the query criteria increases.

On Kibana's Discover tab, we usually use KQL to create search criteria using operators. For example, to search for "2nd edition Java book written by Bert, released after 2010", the equivalent query written in the Discover tab's KQL box is as follows:

```
title:Java and author :Bert and edition:2 and release_date>=2000-01-01
```

