Listing 4.22 Fetching restaurants around a geographical location

```
GET restaurants/_search
{
  "query": {
    "geo_bounding_box":{
      "address":{
        "top_left":{
          "lon":"0",
          "lat":"52"
        },
        "bottom_right":{
          "lon":"1",
          "lat":"50"
        }
      }
    }
  }
}
```

Top-left corner of the box

Bottom-right corner of the box

The query fetches our Sticky Fingers restaurant because it falls in the geo-bounding box represented by the two geopoints.

> **NOTE** When searching for an address using `geo_bounding_box`, a common mistake is providing incorrect inputs (`top_left` and `bottom_right`) to the query. Make sure the longitude and latitudes of these two inputs form the bounding box.

Earlier, I mentioned that we can provide location information in various formats, not just longitude and latitude, including as an array or a string. Table 4.3 lists these formats.

Table 4.3 Location information-related formats

Format	Explanation	Example
Array	Geopoint represented as an array. Note the order of the geopoint inputs: it takes `lon` and `lat`, not the other way around (unlike the string format—see the next row).	`"address":[0.12,51.5]`
String	Geopoint as string data with `lat` and `lon` inputs.	`"address":"51.5,0.12"`
Geohash	An encoded string formed by hashing the longitude and latitude coordinates. The alphanumeric string points to a place on earth.	`u10j4`
Point	A precise location on a map. Known as well-known text (WKT), a standard mechanism to represent geometrical data.	`POINT(51.5,-0.12)`

In this section, we have worked with geo-queries without prior knowledge about them. We cover this topic in detail in chapter 12.