consumption but is designed to produce output in a tabular (columnar) format that is easy on the human eye.

You can find the list of endpoints exposed by the `_cat` API by visiting http://localhost:9200/_cat in your browser or executing this `curl` command:

```
curl 'localhost:9200/_cat'
```

Doing so returns over three dozen endpoints (we show only a few for brevity):

```
/_cat/shards
/_cat/shards/{index}
/_cat/nodes
/_cat/indices
/_cat/indices/{index}
/_cat/count
/_cat/count/{index}
/_cat/health
/_cat/aliases
...
```

Let's determine the cluster's health using the `_cat` API. Visit http://localhost:9200/_cat/health or issue this curl command:

```
curl 'localhost:9200/_cat/health'
```

The `/_cat/health` endpoint exposes the cluster's health. The response to this query is something like the following:

```
1615669944 21:12:24 elasticsearch yellow 1 1 1 1 0 0 1 0 - 50.0%
```

This is a columnar representation of data, but as you can see, there are no column headings to identify the values. You can ask for output with column headings by adding a `v` (for *verbose*) at the end of the query:

```
curl 'localhost:9200/_cat/health?v'
```

This yields the following:

```
epoch      timestamp cluster       status node.total node.data shards pri
     relo init unassign pending_tasks max_task_wait_time
     active_shards_percent
1615669875 21:11:15  elasticsearch yellow          1         1      1   1
     0    0        1             0                  -                  50.0%
```

The response indicates that the cluster name is `elasticsearch` (third field), its status is YELLOW (fourth field), and so on.

A.2 Installing Kibana

Now that Elasticsearch is installed and up and running, you need to install Kibana. The installation follows the same path as for Elasticsearch, and we briefly go through the process for Windows and Mac.