A.2.3 Kibana on macOS

Once the binary is extracted, execute the Kibana shell script to run it:

```
$>cd <KIBANA_INSTALL_DIR>/bin
$>./kibana
```

Changes to the bin directory of the installation

Starts the Kibana dashboard by executing the script

This starts your Kibana dashboard on default port 5601. You should see the following output in the terminal:

```
Status changed from yellow to green - Ready
log [23:17:16.980] [info][listening] Server running at http://localhost:5601
log  [23:17:16.987] [info][server][Kibana][http] http server running at
http://localhost:5601
```

As the log indicates, visiting http://localhost:5601 will land on Kibana's home page (see figure A.3) by default.

A.2.4 Installing via Docker

Similar to the installation of Elasticsearch, there are two ways to work with Docker, as described here.

USING THE DOCKER IMAGE

Elastic publishes its Docker images in the https://www.docker.elastic.co repository. Pull the image from Elastic's docker repo:

```
docker pull docker.elastic.co/elasticsearch/elasticsearch:8.6.2
```

This fetches the image to your local machine. Once the image is downloaded, you can start your engine by running the following commands:

```
docker network create elastic
docker run --name es01-test --net elastic -p 9200:9200 -p 9300:9300 -e
"discovery.type=single-node"
docker.elastic.co/elasticsearch/elasticsearch:7.14.0
```

Creates a local network

Runs the container

This command starts the web server on port 5601, connecting to Elasticsearch search on 9200. Once the command executes successfully, visit http://localhost:5601 on your browser to see the web application in action.

USING DOCKER-COMPOSE

The book's files include Docker files in the docker folder at http://mng.bz/5wvD or on the book's website. Copy (or check out to your local machine) the elasticsearch-docker-8-6-2.yml file. Issue the following command at the terminal:

```
docker-compose up -f elasticsearch-docker-8-6-2.yml
```

This starts both Elasticsearch and Kibana in the Docker container.