```
        "_index": "_index",
        "_id": "_id",
        "_version": "-3",
        "_source": {
          "category": "confidential",
          "op_name": "Operation Cobra"
        },
        "_ingest": {
          "timestamp": "2022-11-03T23:42:33.379569Z"
        }
      }
    }
  ]
}
```

The `_source` object consists of our modified document: the pipeline adds the `category` field. This is the magic of the `set` processor.

As we discussed earlier, we can chain processors. Say we wish to uppercase the stamp ("CONFIDENTIAL"); all we need to do is add another processor—aptly called `uppercase`—to the pipeline and rerun the query.

Listing B.3 Chaining a second processor to uppercase a field

```
PUT _ingest/pipeline/confidential_files_pipeline
{
  "description": "Stamp confidential on the file (document)",
  "processors": [
    {
      "set": {
        "field": "category",
        "value": "confidential"
      },
      "uppercase": {
        "field": "category"
      }
    }
  ]
}
```

The uppercase processor is the new addition.

We added an `uppercase` processor so the two processors are chained: the output from the first processor becomes the input to the second processor. The result is as follows:

```
"_source": {
  "category": "CONFIDENTIAL",
  "op_name": "Operation Cobra"
}
```

The `category` field is added by the `set` processor, and the field is uppercased by the `uppercase` processor, yielding the `CONFIDENTIAL` stamp on the final document. In the next section, let's look at a practical example of loading PDFs using an ingest pipeline.