Listing 6.34 Component template with a mapping schema

```
POST _component_template/dev_mapping_component_template
{
  "template": {
    "mappings": {
      "properties": {
        "created_by": {
          "type": "text"
        },
        "version": {
          "type": "float"
        }
      }
    }
  }
}
```

The `dev_mapping_component_template` consists of a mapping schema predefined with two properties, `created_by` and `version`.

Now that we have two component templates, the next step is to put them to use. We can do this by letting an index template for, say, `cars`, use them.

Listing 6.35 Index template composed of component templates

```
POST _index_template/composed_cars_template
{
  "index_patterns": ["*cars*"],
  "priority": 200,
  "composed_of": ["dev_settings_component_template",
                  "dev_mapping_component_template"]
}
```

The highlighted `composed_of` tag is a collection of all component templates we want to apply. In this case, we choose the settings and mappings component templates.

After the script is executed, if we create an index with *cars* in the index name (`vintage_cars`, `my_cars_old`, `cars_sold_in_feb`, etc.), the index is created with the configuration derived from both component templates. To create a similar pattern in a production environment, for example, we can create a composable template with a `prod_*` version of the component templates.

So far, we have worked with CRUD operations on indexes and instantiated those indexes using templates. However, we have no visibility on index performance. As the next section discusses, Elasticsearch provides statistics on data that's been indexed, deleted, and queried.

6.7 Monitoring and managing indexes

Elasticsearch provides detailed statistics on the data that goes into indexes as well as what is pulled out. It provides APIs to generate reports such as the number of docu-