Listing 6.37 Fetching statistics for multiple indexes

```
GET cars1,cars2,cars3/_stats
```

We can also use wildcards on indexes, as shown next.

Listing 6.38 Fetching statistics using wildcards

```
GET cars*/_stats
```

And here is how to get the stats for all the indexes in the cluster (including hidden indexes).

Listing 6.39 Fetching statistics for all indexes in the cluster

```
GET */_stats
```

We may not need to find all the statistics all the time, so we can, for example, find only the certain statistics about segments such as stored fields and terms memory, file size, document count, and so on. The following listing returns the statistics in segments.

Listing 6.40 Segment statistics

```
GET cars/_stats/segments
```

This command returns the following data:

```
"segments" : {
        "count" : 1,
        "memory_in_bytes" : 1564,
        "terms_memory_in_bytes" : 736,
        "stored_fields_memory_in_bytes" : 488,
        "term_vectors_memory_in_bytes" : 0,
        "norms_memory_in_bytes" : 64,
        "points_memory_in_bytes" : 0,
        "doc_values_memory_in_bytes" : 276,
        "index_writer_memory_in_bytes" : 0,
        "version_map_memory_in_bytes" : 0,
        "fixed_bit_set_memory_in_bytes" : 0,
        "max_unsafe_auto_id_timestamp" : -1,
        "file_sizes" : { }
      }
```

While we're on the subject, Elasticsearch provides an index segments API to peek into the lower-level details of segments. Invoking the code `GET cars/_segments` provides a detailed view of segments managed by Apache Lucene, such as the list of segments and the number of documents (including deleted documents) the segment holds, disk space, whether the segment is searchable, and so on (see figure 6.9). We can also get the segment information across the entire index by invoking the `GET _segments` call.