```
GET <index_name>/_search
{
  "aggregations|aggs": {
    "NAME": {
      "AGG_TYPE": {}
    }
  }
}
```

The `aggs` object tells Elasticsearch that the query invocation is an aggregation type. The `NAME` attribute, provided by the user, gives a suitable name for the aggregation. Finally, `AGG_TYPE` is the type of aggregation: `sum`, `min`, `max`, `range`, `terms`, `histogram`, and so on.

13.1.2 Combining searches and aggregations

We can also combine aggregations with queries. For example, we can run a query to fetch results and then run aggregations on that result set. These are called *scoped aggregations* because the input is the query's result. The syntax is slightly extended from the previous aggregation query:

```
GET <index_name>/_search
{
  "query": {
    "QUERY_TYPE": {
      "FIELD": "TEXT"
    }
  },
  "aggs": {
    "NAME": {
      "AGG_TYPE": {}
    }
  }
}
```

The scope of the aggregation is defined by the query's output. If we don't associate a query with an aggregation request, it is assumed that it will work on all the documents of the index (or indexes) defined in the request URL.

13.1.3 Multiple and nested aggregations

In addition to running solo aggregations, we can execute multiple aggregations on the given data set. This feature is extremely handy if we need to extract analytics on various fields with multiple conditions. For example, we may want to create a histogram of iPhone 14 sales per day as well as a `sum` aggregation of total sales for the month. To do this, we can employ the `histogram` bucketing aggregation and the `sum` metric aggregation.

Additionally, sometimes we need to nest aggregations; for example, the bucketed data in a histogram may need further categorizing (bucketing) of data by date or by finding the minimum and maximum for each bucket. In this case, the aggregated data