want to run our single-field `avg` metric is called `field`. When the query is executed, we get the following results:

```
"aggregations" : {
  "tv_average_price" : {
    "value" : 1555.3333333333333
  }
}
```

The engine calculates the average price of all TVs and returns it to the user. The average TV price across all six documents is about £1555.

13.2.4 The sum metric

The single-value `sum` metric adds the values of the field in question and produces an end result. For example, to find the total value of all TVs sold, we can issue the following query.

Listing 13.4 Total sum of all TVs sold

```
GET tv_sales/_search
{
  "size": 0,
  "aggs": {
    "tv_total_price": {
      "sum": {
        "field": "price_gbp"
      }
    }
  }
}
```

The `sum` metric adds all the prices and produces a single figure of £13,998 when we run the query. Similarly, let's look at the minimum and maximum metric functions next.

13.2.5 The min and max metrics

Sometimes we need to find the minimum and maximum quantities from a set of values, such as the *minimum* number of available speakers for a conference or the session with the most attendees. Elasticsearch exposes the corresponding metrics in the form of `min` and `max` to produce these extremes of a data set. The metrics are self-explanatory, but in the interest of completeness, let's look at them briefly.

Minimum metric

Suppose we want to find the cheapest TV in our stock. This clearly is a candidate for using the `min` metric on the data values.