Listing 13.5 Cheapest price for the TVs

```
GET tv_sales/_search
{
  "size": 0,
  "aggs": {
    "cheapest_tv_price": {
      "min": {
        "field": "price_gbp"
      }
    }
  }
}
```

Calculates the minimum value

Applies the min function to this field

The `min` keyword fetches the metric, which works on the `price_gbp` field to produce the expected result: the field's minimum value derived from all the documents. We fetch the lowest-priced TV (£999) in our stock by executing the query.

MAXIMUM METRIC

We can use similar logic to fetch the best-selling TV: the TV with the *maximum* number of sales.

Listing 13.6 Best-selling TV

```
GET tv_sales/_search
{
  "size": 0,
  "aggs": {
    "best_seller_tv_by_sales": {
      "max": {
        "field": "sales"
      }
    }
  }
}
```

When we execute the query, it returns a TV that sells very quickly (maximum sales). From the results, it is LG's 8K TV with 48 sales.

13.2.6 The stats metric

While the previous metrics are single-value (meaning they work only on a single field), the `stats` metric fetches all common statistical functions. It is a multi-value aggregation that fetches several metrics (`avg`, `min`, `max`, `count`, and `sum`) simultaneously. The query in the next listing applies the `stats` aggregations to the `price_gbp` field.

Listing 13.7 All the common stats at once

```
GET tv_sales/_search
{
  "size": 0,
  "aggs": {
```