```
    "common_stats":{
      "stats": {
        "field": "price_gbp"
      }
    }
  }
}
```

The stats function

Applies stats to this field

Once executed, this query returns the following results:

```
"aggregations" : {
  "common_stats" : {
    "count" : 6,
    "min" : 999.0,
    "max" : 1800.0,
    "avg" : 1299.6666666666667,
    "sum" : 7798.0
  }
}
```

The `stats` metric returns all five metrics simultaneously. This makes it handy if we want to see the basic aggregations all in one place.

13.2.7 The extended_stats metric

Although `stats` is a useful, common metric, it doesn't provide advanced analytics such as variance, standard deviation, and other statistical functions. Elasticsearch includes another metric called `extended_stats` out of the box, which is the cousin of `stats` and deals with advanced statistical metrics.

The `extended_stats` metric provides three stats in addition to the standard statistical metrics: `sum_of_squares`, `variance`, and `standard_deviation`. The following listing demonstrates.

Listing 13.8 Advanced (extended) stats on the `price_gbp` field

```
GET tv_sales/_search
{
  "size": 0,
  "aggs": {
    "additional_stats":{
      "extended_stats": {
        "field": "price_gbp"
      }
    }
  }
}
```

Applying the extended_stats function fetches advanced statistical measures.

Uses extended_stats on this field

We invoke the `extended_stats` function on the `price_gbp` field. Doing so retrieves all the statistical data shown in figure 13.1. The query calculates a lot of advanced statistical information on `price_gbp` as well as common metrics (`avg`, `min`, `max`, etc.) and various variances and standard deviations.