The dis_max query is a compound query that expects a number of leaf queries defined in the queries object. Here, we declare two match queries, searching for multiple words in two different fields: type and overview.

When searching for multiple words across multiple fields, Elasticsearch uses the *best-fields strategy*, which favors a document with all the words in the given fields. For example, suppose we are searching for "smart TV" across two fields, overview and type. We can expect that a document with this phrase in both fields is more relevant than a document with "smart" in the overview field and "TV" in the type field.

When executing a dis_max query on multiple fields, we can also consider scores from other matching queries. In this case, we use a tiebreaker to add the scores from other field matches, not just the best fields. Let's add the tie_breaker attribute to the following query.

Listing 11.23 A dis_max query with a tiebreaker

```
GET products/_search
{
  "_source": ["type","overview"],
  "query": {
    "dis_max": {
      "queries": [{
        "match": {
          "type": "smart tv"
        }
      },
      {
        "match": {
          "overview": "smart TV"
        }
      },
      {
        "match": {
          "product": "smart TV"
        }
      }],"tie_breaker": 0.5
    }
  }
}
```

The tie_breaker value is a positive floating-point number between 0.0 and 1.0 (the default is 0.0). In this case, we multiply the non-best fields' scores by the tiebreaker and add the result to the score of each document that matches multiple fields.

The final compound query we look at in this chapter is the function score query. It gives us much more flexibility when assigning scores based on our needs using predefined functions.

11.7 The function_score query

Sometimes we want to assign a score to a returned document from a search query based on in-house requirements, such as giving weight to a particular field or displaying a