requirements. For example, if we want a randomly generated score, there's a simple `random_score` function query for that purpose. Or we may want to compute the score based on field values and parameters, in which case we can use a `script_score` function query. We also look at a couple other functions in this section, but let's start with `random_score`.

11.7.1 The random_score function

As the name suggests, the `random_score` function creates a randomly generated score for the resulting documents. We can run the query from listing 11.25, wrapped in a `function_score` query, but this time specifically assign a `random_score` function to the query.

Listing 11.26 Term search wrapped in a `random_score` function

```
GET products/_search
{
  "query": {
    "function_score": {
      "query": {
        "term": {
          "product": "TV"
        }
      },
      "random_score": {}
    }
  }
}
```

A function_score with a term query and a function

A random_score function that generates and assigns a random score for each call

This `function_score` query is made of a `term` query and a `random_score` function. Every time we execute this query, we get a different score for the same returned document. The random scores are, well, random and can't be reproduced. When you re-execute the query, expect the score to change.

What if we have a requirement to reproduce the random score so that no matter how many times we execute the same query, the randomly generated score is always the same? For this purpose, we can tweak the `random_score` function by priming it with `seed` and `field` values. The following listing shows the query with a `random_score` function initialized with a `seed`.

Listing 11.27 Tweaking random scores by setting a `seed`

```
GET products/_search
{
  "query": {
    "function_score": {
      "query": {
        "term": {
          "product": "TV"
        }
```