```
        },
        "random_score": {
          "seed": 10,
          "field":"user_ratings"
        }
      }
    }
}
```

Initializes the customized random_score with a seed

Computes the random score

As you can see, `random_score` is initialized with a `seed` value and a `user_ratings` `field` value. If we execute this query more than once, we are guaranteed to get the same (albeit random) score. The algorithm and mechanics to determine the random score are beyond the scope of this book; consult the Elasticsearch documentation if you want to understand more about random scoring mechanics.

While the `random_score` function is one way to generate a random score, generating a static score using a scripting function is also interesting. In the next section, let's look at how we can use the `script_score` function.

11.7.2 The script_score function

Suppose we want to triple-boost the document score (multiply the field's value by a factor of 3) based on a field's value (for example, the `user_rating` of a product). In this instance, we can use a `script_score` function to compute the score based on the values of other fields (such as `user_ratings`) in the document.

Listing 11.28 Multiplying the field's value by an external parameter

```
GET products/_search
{
  "query": {
    "function_score": {
      "query": {
        "term": {
          "product": "tv"
        }
      },
      "script_score": {
        "script": { #B
          "source":"_score * doc['user_ratings'].value * params['factor']",
          "params": {
            "factor":3
          }
        }
      }
    }
  }
}
```

The script_score function holds the key to generating a score based on its defined script.

The script object

Passes the external parameters to the script

The source is where we define our logic.

The `script_score` function produces a score, and in this example it calculates that score based on a simple script calculation: find `user_ratings` and multiply the value