by the original score and `factor` (passed via external `params`). We can construct a complicated query based on a fully fledged script if needed.

Scripts can create a complex scenario with parameters, field values, and mathematical functions (for example, the square root of the average user ratings multiplied by a given `boosting` factor). However, not every requirement needs such a complicated script. If our requirement is just to use a field's value, a simple way to get the result is to use a function called `field_value_factor`.

### 11.7.3 The field_value_factor function

The `field_value_factor` function helps achieve scoring by using fields without the complexity of scripting. The following listing shows the mechanism.

**Listing 11.29 Deriving the score from a field without scripting**

```
GET products/_search
{
  "query": {
    "function_score": {
      "query": {
        "term": {
          "product": "tv"
        }
      },
      "field_value_factor": {
        "field": "user_ratings"
      }
    }
  }
}
```

The field_value_factor object that declares the field (user_ratings, in this case)

The script shows that the `field_value_factor` function works on a field (`user_ratings` in this listing) to produce a new relevancy score.

We can add attributes to the `field_value_score` function. For example, we can multiply the score by using a `factor` attribute and applying a mathematical function such as a square root or a logarithmic calculation. The next listing shows this in action.

**Listing 11.30 Additional attributes on `field_value_factor`**

```
GET products/_search
{
  "query": {
    "function_score": {
      "query": {
        "term": {
          "product": "tv"
        }
      },
      "field_value_factor": {
```