```
      "ctx._source.actors.remove(ctx._source.actors.indexOf('Diane Keaton'))"
  }
}
```

The remove method expects the integer position of the actor.

`ctx._source.actors.indexOf('Diane Keaton')` returns an index of the element in the `actors` array. This is *required* for the `remove` method.

ADDING A NEW FIELD

We can also add a new field to our document using a script like that in the following listing. Here we add a new field, `imdb_user_rating`, with a value of `9.2`.

Listing 5.25 Adding a new field with a value using a script

```
POST movies/_update/1
{
  "script": {
    "source": "ctx._source.imdb_user_rating = 9.2"
  }
}
```

NOTE To add a new value to an array (as we did in listing 5.23), we invoke the `add` method on the array: `ctx._source.<array_object>.add('value')`

REMOVING A FIELD

Removing a field is also a straightforward job. The following listing removes a field (`imdb_user_rating`) from our `movies` document.

Listing 5.26 Removing a field from the source document

```
POST movies/_update/1
{
  "script": {
    "source": "ctx._source.remove('imdb_user_rating')"
  }
}
```

NOTE If we try to remove a nonexistent field, we do not get an error message letting us know that we are trying to remove a field that doesn't exist on the schema. Instead, we get a response indicating that the document was updated and the field was incremented (which I consider a false positive).

ADDING MULTIPLE FIELDS

We can write a script that adds multiple fields at once.

Listing 5.27 Adding multiple new fields using a script

```
POST movies/_update/1
{
  "script": {
    "source": """
```