GET method 29, 162, 171, 289
GET request 163, 200, 204
glob (global command) pattern 212, 482
Gough, Jame 490
GPT (generative pretrained transformer) 17
gt (greater than) operator 128, 323
gte (greater than or equal to) operator 128, 323

H

hash function 96
HDDs (hard disk drives) 498
HDFS (Hadoop Distributed File System) 14, 478
HEAD <index_name> command 208
HEAD request 163
heap 498
hidden indexes 208
high-disk watermark 510
high-level architecture 61–67
  data in 62–63
  data out 66–67
  processing data 63–66
    analyzing data 64–66
    collecting data 63
    types of data 64
highlight object 43, 300
highlighting 43, 299–301
histogram aggregation 446, 452
histogram buckets 56–57, 446
histograms 446–450
  date histogram 447–448
  interval setup for date histogram 448–450
hits array 539
hits attribute 291
hmtl_strip filter 266–267
horizontal scaling 98, 477
hot_delete_policy policy 230
hot_delete_policy_index index 230
html_strip character filters 240, 258, 266
html_strip filter 260, 266
HTTP DELETE action 483
HTTP DELETE method 181
HTTP HEAD action 163
HTTP POST action 156
HTTP POST method 151, 154
HTTP PUT method 23, 29, 151, 154

I

IaC (infrastructure as code) tools 98
ID (identifier) 151
id method 537
IDF (inverse document frequency) 90, 92, 302
ids API query 32
ids object 33
ids query 33, 165–166, 321–322
IDs term-level query 47, 315
IDs, retrieving multiple documents by 33–34
ILM (index lifecycle management) 227–234
  lifecycle 228–229
  lifecycle with rollover 231–234
  managing manually 229–230
implict (automatic) index creation 194–198
  configurations 197–198
  disabling auto-creation 196–197
in_order flag 418
include_global_state attribute 485
includes array 310
index action 53, 185
index method 537
index object 201
index operation 40
index package 489
index_prefixes object 330
index_prefixes parameter 329
index-level analyzers
  specifying for indexes 262–263
  specifying for search 264–265
index.blocks.write property 223
index.lifecycle.name 230
index.lifecycle.rollover_alias name 232
index.max_terms_count property setting 319
index.number_of_replicas property 223
index.routing.allocation.require.property 224
index() method 535
index/_id pair 165
indexes 192–234
  clients 534–538
  closing 210–212
    avoiding destabilizing system 211
    closing all or multiple indexes 211
  creating 193–207
    aliases 202–207
    custom settings 198–201
    explicitly 198
    implicitly (automatic creation) 194–198
    mappings 201–202
  deleting 209–210
    deleting multiple indexes 209–210
    deleting only aliases 210
  index speed problems 503–506
    adjusting refresh rate 503–506
    bulk requests 503
    system-generated identifiers 503
  indexing documents 23–26, 150–161
    constituents of requests 29–30
    cURL 24–26
    customizing refresh process 160–161
    document APIs 23–24, 151–158
    in bulk 186–188
    mapping 103–104