(continued)

Stemmers are language dependent. For example, we can employ a French stemmer if the chosen language of the documents is French. Stemmers are declared via token filters when composing the analyzer module during the text analysis phase in Elasticsearch.

The same process is retriggered during execution of search queries on the same field. Chapter 7 is dedicated to the analysis of full text and discusses the intricacies of analyzers and how Elasticsearch manages full-text data.

We mentioned earlier that Elasticsearch defines types microscopically: for example, further classifying `text` fields into more specific types such as `search_as_you_type`, `match_only_text`, `completion`, `token_count`, and others. Let's examine these specialized text types briefly in the next few sections to see how Elasticsearch puts extra emphasis and effort into full text.

THE TOKEN_COUNT DATA TYPE

A specialized form of the `text` data type, `token_count`, defines a field that captures the number of tokens in that field. For example, if we have defined a book's `title` as a `token_count`, we can retrieve all books based on the number of tokens a book has. Let's create a mapping for this by creating an index with a `title` field.

Listing 4.9 Index with a `token_count` data type for the `title` field

```
PUT tech_books
{
  "mappings": {
    "properties": {
      "title": {
        "type": "token_count",
        "analyzer": "standard"
      }
    }
  }
}
```

The field's name

The title's data type is token_count.

The analyzer is expected to be provided.

As you can see, `title` is defined as a `token_count` type. The analyzer is expected to be provided, so we set the standard analyzer on the `title` field. Now, let's index three technical books—this one and my future (hopefully) books—before searching for them based on the title's token count feature.

Listing 4.10 Indexing three new documents into the `tech_books` index

```
PUT tech_books/_doc/1
{
  "title":"Elasticsearch in Action"
}
```