```
PUT tech_books/_doc/2
{
  "title":"Elasticsearch for Java Developers"
}

PUT tech_books/_doc/3
{
  "title":"Elastic Stack in Action"
}
```

Now that the `tech_books` index contains a few books, let's put the `token_count` type to use. The following `range` query fetches books with titles composed of more than three words (`gt` is short for greater than) but fewer than or equal to five words (`lte` is short for less than or equal to).

Listing 4.11 `range` query fetching books with a certain number of words

```
GET tech_books/_search
{
  "query": {
   "range": {
     "title": {
       "gt": 3,
       "lte": 5
     }
   }
  }
}
```

The `range` query fetches books based on the number of words in the title. It retrieves *Elasticsearch for Java Developers* (four tokens) and *Elastic Stack in Action* (four tokens) but omits *Elasticsearch in Action* (three tokens).

We can also combine the `title` field as a `text` type and a `token_type`, as Elasticsearch allows a single field to be declared with multiple data types (multi-fields—discussed in detail in section 4.7). The following listing creates a new index (`tech_books2`) using this technique.

Listing 4.12 Adding `token_count` as an additional data type to a `text` field

```
PUT tech_books2
{
  "mappings": {
    "properties": {
      "title": {
        "type": "text",
        "fields": {
          "word_count": {
            "type": "token_count",
            "analyzer": "standard"
          }
        }
```

The title field is defined as text data type.

The title field is declared to have multiple data types.

word_count is the additional field.

The type of word_count

It is mandatory to provide the analyzer.