```
PUT census/_doc/1
{
  "name":"John Doe"
}
```

When we search for all residents of the UK, even though the document doesn't have that field during indexing, we receive a positive result that returns John's document:

```
GET census/_search
{
  "query": {
    "term": {
      "country": {
        "value": "United Kingdom"
      }
    }
  }
}
```

The `constant_keyword` field will have exactly the same value for every document in that index.

THE WILDCARD DATA TYPE

The `wildcard` data type is another special data type that belongs to the `keyword` family. It supports searching data using wildcards and regular expressions. We define a field as a `wildcard` type by declaring it as `"type": "wildcard"` in the mapping definition. We then query the field by issuing a `wildcard` query, as shown in listing 4.16.

> **NOTE** A document with `"description":"Null Pointer exception as object is null"` was indexed before this query.

Listing 4.16 A `wildcard` query with a wildcard value

```
GET errors/_search
{
  "query": {
    "wildcard": {
      "description": {
        "value": "*obj*"
      }
    }
  }
}
```

Uses a wildcard query

Searches using wildcards

Keyword fields are efficient and performant, so using them appropriately improves indexing and search query performance.

4.5.3 The date data type

Elasticsearch provides a `date` data type to support indexing and searching date-based operations. Date fields are considered structured data, so we can use them in sorting, filtering, and aggregations.