The `date_range` type field expects two values: an upper bound and a lower bound. These are usually represented by abbreviations like `gte` (greater than or equal to), `lt` (less than), and so on.

With the data prepped, let's issue a search request to find Venkat's courses between two dates.

Listing 4.19 Searching for courses between two dates

```
GET trainings/_search
{
  "query": {
    "range": {
      "training_dates": {
        "gt": "2021-08-10",
        "lt": "2021-08-12"
      }
    }
  }
}
```

We use a range query to search.

Searches for courses between these two dates

In response to the query (the results are skipped for brevity), we learn that Venkat is delivering a "Programming Kotlin" training between the two dates (the second document matches the dates). The `date_range` made it easy to search a range of data. In addition to `date_range`, we can create other ranges including `ip_range`, `float_range`, `double_range`, `integer_range`, and so on.

4.5.7 The IP address (ip) data type

Elasticsearch provides a specific data type to support internet protocol (IP) addresses: the `ip` data type. This data type supports both IPv4 and IPv6 IP addresses. To create a field of `ip` type, use `"field":{"type": "ip"}` as the following example shows:

```
PUT networks
{
  "mappings": {
    "properties": {
      "router_ip":{ "type": "ip" }
    }
  }
}
```

The field's data type is ip.

Indexing the document is straightforward:

```
PUT networks/_doc/1
{
  "router_ip":"35.177.57.111"
}
```

Indexes a document with an IP address

Finally, we can use our search endpoint to search for IP addresses that match our query. The following query searches for data in the `networks` index to get the matching IP address: