migration completes successfully. To manually re-enable refresh on the index, we simply issue a `POST <index>/_refresh` command.

CLIENT-SIDE REFRESH CONTROLS

We can also control the refresh operation from the client side for CRUD operations on documents by setting the `refresh` query parameter. The document APIs (`index`, `delete`, `update`, and `_bulk`) expect `refresh` as a query parameter. For example, the following snippet advises the engine to start the refresh once the document has been indexed as opposed to waiting for the refresh interval to expire:

```
PUT movies/_doc/1?refresh
```

The `refresh` query parameter can have three values:

- `refresh=false` *(default)*—Tells the engine not to force the refresh operation but instead to apply the default setting (one second). The engine makes the document available for search only after the predefined refresh interval. We can also not provide the query parameter, which achieves the same effect.

  Example: `PUT movies/_doc/1?refresh=false`
- `refresh=true` *(or empty string)*—Forces the refresh operation so the document is visible for searching immediately. If our refresh time interval is set to 60 seconds and we index 1,000 documents with `refresh=true`, all 1,000 documents should be available to search instantly rather than waiting for the 60-second refresh interval.

  Example: `PUT movies/_doc/1?refresh=true`
- `refresh=wait_for`—A blocking request that compels the client to wait until the refresh operation kicks in and completes before the request is returned. For example, if our refresh interval is 60 seconds, the request is blocked for 60 seconds until the refresh is performed. However, it can be manually started by invoking the `POST <index>/_refresh` endpoint.

  Example: `PUT movies/_doc/1?refresh=wait_for`

We also need to understand the mechanics of retrieving documents. Elasticsearch provides a `GET` API for reading documents, which is similar to the indexing APIs we saw previously. The next section looks at the mechanics of reading documents from the Elasticsearch stash.

5.2 Retrieving documents

Elasticsearch provides two types of document APIs for retrieving documents:

- A single-document API that returns one document, given an ID
- A multi-document API that returns multiple documents, given an array of IDs

If a document is not available, we receive a JSON response indicating that the document is not found. Let's see how to retrieve documents using both APIs.