If we pause the refresh, we exclude any of the latest indexed documents: they are not available for searches. We essentially minimize the resource-intensive operation of disk I/O. For example, if we pause the refresh operation for 1 minute, we potentially stop 60 rounds of disk sync. The downside is that any search queries during this period do not pick up the new documents indexed during this minute.

For example, if our use case allows holding the refresh for a defined period of time, we can reset the default refresh period by invoking the setting on the index. The following listing shows the code.

Listing 15.7 Customizing the refresh setting

```
PUT programming_books3/_settings
{
  "index":{
    "refresh_interval":"1m"
  }
}
```

Sets a custom value (here, 1 minute) for the refresh cycle

Here, we set a one-minute interval for the refresh, so any books added during this minute aren't available for searching. A usual practice is to turn off the refresh operation before indexing. The next listing shows how we can turn off refresh completely.

Listing 15.8 Disabling refresh

```
PUT programming_books3/_settings
{
  "index":{
    "refresh_interval":-1
  }
}
```

By setting `refresh_interval` to `-1`, we essentially disable the refresh operation. Any documents that are indexed after we disable refresh are not available for searches. If you are curious about this setting's side effects, index a document and issue a search, as the following listing shows. The search should yield no results.

Listing 15.9 Searching with a disabled refresh index

```
PUT programming_books3/_doc/10
{
  "title":"Elasticsearch for Java Developers",
  "synopsis":"Elasticsearch meets Java"
}

GET programming_books3/_search
{
  "query": {
    "match": {
```

Indexes a sample document

Searching when refresh is disabled returns no result.