Table A.1 Elasticsearch folder structure *(continued)*

Folder name	Details
logs	Directory where our running Elasticsearch instance spits out logging data, including server and garbage collection logs
data	Folder to which data is written, like a persistence store. All documents are stored here on the computer's filesystem.

Once the binary is extracted to your folder, start a command prompt with administrative privileges. At the command prompt, issue a change directory (`cd`) command to move into Elasticsearch's bin folder:

```
cmd>cd <INSTALL_DIR>\elasticsearch\bin
Execute the elasticsearch.bat to start up the server:
cmd> elasticsearch.bat
```

If all goes well, you should see output like "Server Started" printed on the console. Here, we started our server as a single-node instance. Once it is started up, it joins a cluster automatically with one node (itself). The server is available by default at https://localhost:9200 (default settings).

Open your web browser, and visit the Elasticsearch home page at https://localhost:9200. If the server is running happily, a JSON response will come back from the server, as shown in figure A.1. This simple "success" message from Elasticsearch indicates that the server is alive and running.


```
{
  "name": "mkmac.local",
  "cluster_name": "elasticsearch",
  "cluster_uuid": "h1KA7SGER-qKS3l821YA1Q",
  "version": {
    "number": "8.4.2",
    "build_flavor": "default",
    "build_type": "tar",
    "build_hash": "89f8c6d8429db93b816403ee75e5c270b43a940a",
    "build_date": "2022-09-14T16:26:04.382547801Z",
    "build_snapshot": false,
    "lucene_version": "9.3.0",
    "minimum_wire_compatibility_version": "7.17.0",
    "minimum_index_compatibility_version": "7.0.0"
  },
  "tagline": "You Know, for Search"
}
```


Figure A.1 The Elasticsearch server's home page