```
          "exists": {
            "field": "confidential"
          }
        }
      ]
    }
  }
}
```

We add two documents to the `top_secret_files` index: one of the documents has an additional field called `confidential`. We then write an `exists` query in the `must_not` clause of a `bool` query to fetch all documents that are not categorized as confidential. (We discuss compound queries in chapter 11.)

Sometimes we want to work with data that falls in a certain predefined range: fetching movies from last month, sales in a quarter, highest grossers, etc. These queries are grouped under the heading of `range` queries, which we look at next.

9.6 The range query

Frequently, we need a set of data that falls within a range: flights delayed between certain dates, sales profits on a particular day, pupils of average height in a class, and so on. Elasticsearch provides a `range` query for these types of inquiries.

A `range` query returns documents for a range in a field. The query accepts lower and upper bounds on the field. For example, to fetch all movies with a rating between 9.0 and 9.5, we can execute the following `range` query.

Listing 9.13 Fetching movies with a specified range of ratings

```
GET movies/_search
{
  "query": {
    "range": {
      "rating": {
        "gte": 9.0,
        "lte": 9.5
      }
    }
  }
}
```

This `range` query fetches movies within the specified `rating` limits. A `rating` field is an object that accepts bounds, defined as operators. Table 9.1 shows the operators we can use to specify the range.

We use `range` queries to search across a range of dates or numbers. For example, to fetch all movies made after 1970, we simply stitch together this query.

Table 9.1 Operators in a `range` query

Operator	Meaning
`gt`	Greater than
`gte`	Greater than or equal to
`lt`	Less than
`lte`	Less than or equal to