(continued)

Make sure all the index lines are updated, not just the top one. Alternatively, you can remove the `_index` field completely and add "`index`" to the URL:

```
POST books_new/_bulk
{"index":{"_id":"1"}}
..
```

The example in the text updates the existing `books` index rather than creating a new one, so all the queries in this chapter are performed on the updated `books` index.

The example uses the data sets provided with this book, which are available at GitHub (https://github.com/madhusudhankonda/elasticsearch-in-action) and the book's website (https://www.manning.com/books/elasticsearch-in-action-second-edition). Copy the contents of the books-kibana-dataset.txt file, and paste it into Kibana's Dev Tools. Figure 2.15 shows part of the file's contents.

```
1 POST _bulk
2 {"index":{"_index":"books","_id":"1"}}
3 {"title": "Core Java Volume I - Fundamentals","author": "Cay S. Horstmann","edition": 11, "synopsis": "Java
  reference book that offers a detailed explanation of various features of Core Java, including exception
  handling, interfaces, and lambda expressions. Significant highlights of the book include simple language,
  conciseness, and detailed examples.","amazon_rating": 4.6,"release_date": "2018-08-27","tags": ["Programming
  Languages, Java Programming"]}
4 {"index":{"_index":"books","_id":"2"}}
5 {"title": "Effective Java","author": "Joshua Bloch", "edition": 3,"synopsis": "A must-have book for every Java
  programmer and Java aspirant, Effective Java makes up for an excellent complementary read with other Java books
  or learning material. The book offers 78 best practices to follow for making the code better.", "amazon_rating"
  : 4.7, "release_date": "2017-12-27", "tags": ["Object Oriented Software Design"]}
```

Figure 2.15 Bulk indexing documents using the `_bulk` endpoint

Execute the query, and you should receive an acknowledgment indicating that all the documents were successfully indexed.

Weird-looking bulk indexing document formats

If you look closely at the documents that are loaded using `_bulk`, you will notice some weird syntax. Every two lines correspond to one document, like this:

```
{"index":{"_id":"1"}}
{"brand": "Samsung","name":"UHD","size_inches":65,"price":1400}
```

The first line is metadata about the record, including the operation (`index`, `delete`, `update`) we are about to execute (`index`, in this case), the document ID, and the index where the record is going. The second line is the actual document. We revisit this format in chapter 5 when we discuss document operations.