- `origin`—The focal point (in longitude and latitude) from which to measure the distance
- `pivot`—The distance from the focal point

In listing 12.21, London School of Economics is closer to London Bridge than Imperial College, so London School of Economics is returned at the top of the results with a higher score. Now let's look at using the `distance_feature` query with dates.

BOOSTING THE SCORE USING DATES

In the previous section, a `distance_feature` query helped us search for universities, boosting the score for those nearer to a certain geolocation. A similar requirement can also be satisfied with `distance_feature`: boosting the score of results if they are close to a date.

Suppose we want to search for all iPhone release dates, topping the list with iPhones released within 30 days around December 1, 2020 (for no particular reason other than trying out the concept). We can write a query similar to listing 12.21, except the `field` attribute is based on a date. Let's first create an `iphones` mapping and index a few iPhones.

Listing 12.22 Creating an `iphones` index and priming it with documents

```
PUT iphones
{
  "mappings": {
    "properties": {
      "name":{
        "type": "text"
      },
      "release_date":{
        "type": "date",
        "format": "dd-MM-yyyy"
      }
    }
  }
}

PUT iphones/_doc/1
{
  "name":"iPhone",
  "release_date":"29-06-2007"
}

PUT iphones/_doc/2
{
  "name":"iPhone 12",
  "release_date":"23-10-2020"
}
PUT iphones/_doc/3
{
  "name":"iPhone 13",
  "release_date":"24-09-2021"
}
```

Indexes a few documents