```
"hits" : [
      {
        "_index" : "iphones",
        "_id" : "4",
        "_score" : 1.1876879,
        "_source" : {
          "name" : "iPhone 12 Mini",
          "release_date" : "13-11-2020"
        }
      },
      {
        "_index" : "iphones",
        "_id" : "2",
        "_score" : 1.1217185,
        "_source" : {
          "name" : "iPhone 12",
          "release_date" : "23-10-2020"
        }
      }
    ]
```

The iPhone 12 Mini scores higher than the iPhone 12 because it was released 17 days before our pivot date, while the iPhone 12 was released almost five weeks earlier.

12.9.2 The pinned query

You may have seen sponsored search results at the top of the result set when querying your favorite e-commerce website, such as Amazon. Suppose we want to implement such functionality in our application using Elasticsearch. Fret not: the `pinned` query is at hand.

The `pinned` query adds chosen documents to the result set so they appear at the top of the list. It does so by making their relevance scores higher than the others. The example query in the following listing shows this functionality.

Listing 12.24 Modifying search results by adding sponsored results

```
GET iphones/_search
{
  "query": {
    "pinned":{
      "ids":["1","3"],
      "organic":{
        "match":{
          "name":"iPhone 12"
        }
      }
    }
  }
}
```

Specifies the pinned query

List of document IDs scored higher than the rest of the results

Carries out the query search

A match query that searches for the iPhone 12

This `pinned` query has several moving parts. Let's look at the `organic` block first. The `query` block holds the search query; in this case, we are searching for the iPhone 12 in