Calling the `indices()` function on the `elasticsearchClient` instance returns `ElasticsearchIndicesClient`. Once we have the client, we can invoke the `create()` method to create an index. The `create()` method expects a `CreateIndexRequest` object. This pattern leads to our next request/response pattern.

All methods on the client are expected to be passed in with a request object. There are many request classes, and each request object is instantiated using the builder pattern.

Suppose we need to create an index. This requires a `CreateIndexRequest` to be instantiated with the arguments needed to create an index. The following code creates the `CreateIndexRequest` using a builder:

```
CreateIndexRequest createIndexRequest =
  new CreateIndexRequest.Builder().index("flights").build();
```

The `index()` method accepts a string as the name of the index. Once the index is created, we can invoke the `create()` method on the client by passing this request:

```
CreateIndexResponse createIndexResponse =
       elasticsearchIndicesClient.create(createIndexRequest);
```

This call invokes the `create()` method on `elasticsearchIndicesClient`, which sends a query to the Elasticsearch server to create the index.

The result of this invocation is captured in the response object: `CreateIndexResponse`, in this case. Again, any invocation will return a response following the same pattern—for example, `CreateIndexRequest`'s response is a `CreateIndexResponse` object. The response object has all the required information about the newly created index.

The full method is given in listing C.6. The source code for the entire class along with the project is available with the book's files.

Listing C.6 Creating an index using `ElasticsearchIndicesClient`

```
/**
* Method to create an index using bog-standard ElasticsearchIndicesClient
*
* @param indexName
* @throws IOException
*/
public void createIndexUsingClient(String indexName) throws IOException {
   ElasticsearchIndicesClient elasticsearchIndicesClient =
           this.elasticsearchClient.indices();
   CreateIndexRequest createIndexRequest =
new CreateIndexRequest.Builder().index(indexName).build();

CreateIndexResponse createIndexResponse =
          elasticsearchIndicesClient.create(createIndexRequest);
System.out.println("Index created successfully: "+createIndexResponse);
}
```