The response from the `search()` method is a `SearchResponse`—so we can capture the results as shown here:

```
SearchResponse searchResponse =
     this.elasticsearchClient.search(..)
```

The `searchResponse` consists of results as `hits`, which we can iterate through to get the list of flights that were returned. The following listing shows the entire search request, including the flights returned in the response.

Listing C.13 Searching using the Java API client with hits

```
public void search(String indexName, String field, String searchText) throws
     IOException {

SearchResponse searchResponse =
  this.elasticsearchClient.search(searchRequest -> searchRequest
       .index(indexName)
       .query(queryBuilder -> queryBuilder
                   .match(matchQueryBuilder ->
            matchQueryBuilder
                                .field("route")
                                .query(searchText)))
           ,Flight.class
   );

List<Flight> flights =                          <-- Capture flights ...
  (List<Flight>) searchResponse.hits().hits()
    .stream().collect(Collectors.toList());

searchResponse.hits().hits()
  .stream().forEach(System.out::println);       <-- ... or print them to the console.

}
```

The `searchResponse` object has the results in the `hits` array—we just need to be sure to cast the hits to appropriate domain objects (`Flight`, in this case). The full source code of this example is available with the book's files. You can learn about the other clients in the documentation here: http://mng.bz/QPMQ.