file, secret_organizations.txt (be sure to create this file if you don't have it the config folder). The file must be present in Elasticsearch's config directory (<*INSTALL_DIR*>/elasticsearch/config) or input with an absolute path where it is located.

Listing 7.40 Loading external mappings via a file

```
POST _analyze
{
  "text": "FBI and CIA are USA's security organizations",
  "char_filter": [
    {
      "type": "mapping",
      "mappings_path": "secret_organizations.txt"
    }
  ]
}
```

The secret_organizations.txt sample file should consist of the following data:

```
FBI=>Federal Bureau of Investigation
CIA=>Central Intelligence Agency
USA=>United States of America
```

7.6.4 The pattern_replace character filter

The `pattern_replace` character filter, as the name suggests, replaces a character with a new character when the field matches a regular expression (regex). Following the same code pattern as in listing 7.38, let's create an index with an analyzer associated with a `pattern_replace` character filter.

Listing 7.41 Using a `pattern_replace` character filter

```
PUT index_with_pattern_replace_filter
{
  "settings": {
    "analysis": {
      "analyzer": {
        "my_pattern_replace_analyzer":{
          "tokenizer":"keyword",
          "char_filter":["pattern_replace_filter"]
        }
      },
      "char_filter": {
        "pattern_replace_filter":{
          "type":"pattern_replace",
          "pattern":"_",
          "replacement":"-"
        }
      }
    }
  }
}
```

