Listing 7.43 Index with a custom tokenizer

```
PUT index_with_custom_standard_tokenizer
{
  "settings": {
    "analysis": {
      "analyzer": {
        "custom_token_length_analyzer": {
          "tokenizer": "custom_token_length_tokenizer"
        }
      },
      "tokenizer": {
        "custom_token_length_tokenizer": {
          "type": "standard",
          "max_token_length": 2
        }
      }
    }
  }
}
```

Creates a custom analyzer with a pointer to the custom tokenizer

Custom tokenizer with max_token_length set to two characters

Similar to how we created an index with a custom component for types of character filters in section 7.7.1, we can create an index with a custom analyzer encompassing a `standard` tokenizer. The tokenizer is then extended by providing the `max_token_length` size (in listing 7.43, the length is set to `2`). Once the index is created, we can use the `_analyze` API to test the field.

Listing 7.44 Testing a token size for the tokenizer

```
POST index_with_custom_standard_tokenizer/_analyze
{
  "text": "Bond",
  "analyzer": "custom_token_length_analyzer"
}
```

This code spits out two tokens: "Bo" and "nd", honoring our request for a token size of two characters.

7.7.2 The ngram and edge_ngram tokenizers

Before we jump into learning about n-gram tokenizers, let's recap n-grams, edge n-grams, and shingles. N-grams are sequences of words of a given size prepared from a given word. Take as an example the word *coffee*. The two-letter n-grams, usually called bi-grams, are "co", "of", "ff", "fe", and "ee". Similarly, the three-letter tri-grams are "cof", "off", "ffe", and "fee". As you can see, n-grams are generated by sliding the letter window.

On the other hand, edge n-grams are words with letters anchored at the beginning of the given word. Again using *coffee* as our example, the edge n-grams are "c", "co", "cof", "coff", "coffe", and "coffee". Figure 7.13 shows these n-grams and edge n-grams.