```
          "type":"ngram",
          "min_gram":2,
          "max_gram":3,
          "token_chars":[
            "letter"
          ]
        }
      }
    }
  }
}
```

Using the `min_gram` and `max_gram` attributes of this `ngram` tokenizer (set to `2` and `3`, respectively), we can configure the index to produce n-grams. Let's test this feature.

Listing 7.46 Testing the `ngram` tokenizer

```
POST index_with_ngram_tokenizer/_analyze
{
  "text": "bond",
  "analyzer": "ngram_analyzer"
}
```

This produces the following n-grams: "bo", "bon", "on", "ond", and "nd". The n-grams have two or three characters.

THE EDGE_NGRAM TOKENIZER

Following the same path, we can use the `edge_ngram` tokenizer to spit out edge n-grams. This is the code that creates an analyzer with the `edge_ngram` tokenizer:

```
..
"tokenizer": {
  "my_edge_ngram_tokenizer":{
    "type":"edge_ngram",
     "min_gram":2,
     "max_gram":6,
     "token_chars":["letter","digit"]
   }
}
```

Once the `edge_ngram` tokenizer is attached to a custom analyzer, we can test the field using the `_analyze` API:

```
POST index_with_edge_ngram/_analyze
{
  "text": "bond",
  "analyzer": "edge_ngram_analyzer"
}
```

This invocation spits out these edge n-grams: "b", "bo", "bon", and "bond." Note that all the words are anchored on the first letter.