```
use App\Http\Controllers\ProductController;

Route::get('/product/create', [ProductController::class, 'create'])->name('product.create')
Route::post('/product/result', [ProductController::class, 'result'])->name('product.result
```

Save the file. This will set up the routes for our application.

8.8.4.5 Step 5: Create Views with Bootstrap

We create `product` directory inside `resources/views`:

```
mkdir resources/views/product
```

Then, we create two files: `create.blade.php` and `result.blade.php`.

Here are the contents of each file:

View 1: `resources/views/product/create.blade.php`

```
<!DOCTYPE html>
<html>
<head>
    <title>Create Product (No DB)</title>
    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
rel="stylesheet">
</head>
<body class="container py-5">
    <h2>Create Product</h2>
    <form method="POST" action="{{ route('product.result') }}">
        @csrf
        <div class="mb-3">
            <label class="form-label">Name</label>
            <input name="name" class="form-control" required>
        </div>
        <div class="mb-3">
            <label class="form-label">Price</label>
            <input name="price" type="number" step="0.01" class="form-control" required>
        </div>
        <button type="submit" class="btn btn-primary">Submit</button>
    </form>
</body>
</html>
```

View 2: `resources/views/product/result.blade.php`

```
<!DOCTYPE html>
<html>
<head>
    <title>Product Result</title>
    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
rel="stylesheet">
</head>
<body class="container py-5">
    <h2>Product Summary</h2>
    <ul class="list-group">
```