```
    public function down()
    {
        Schema::dropIfExists('todos');
    }
};
```

This code defines the `todos` table with the following columns:

- `id`: Primary key
- `task`: String column for the task name
- `completed`: Boolean column to indicate if the task is completed

After editing the migration file, we need to run the migration to create the `todos` table in the SQLite database.

Run the migration:

```
php artisan migrate
```

You should see a message indicating that the migration was successful. You can check the `database/database.sqlite` file to confirm that the `todos` table has been created.

10.5.5.4 Step 4: Create a Seeder for Dummy Data

We will create a seeder to populate the `todos` table with some initial data.

Run this command to create a seeder:

```
php artisan make:seeder TodoSeeder
```

This will create a new seeder file in the `database/seeders` directory. Open the generated file in `database/seeders/TodoSeeder.php` and update it:

```
<?php

namespace Database\Seeders;

use Illuminate\Database\Console\Seeds\WithoutModelEvents;
use Illuminate\Database\Seeder;
use Illuminate\Support\Facades\DB;
use Carbon\Carbon;

class TodoSeeder extends Seeder
{
    public function run()
    {
        DB::table('todos')->insert([
            [
                'task' => 'Buy groceries',
                'completed' => false,
                'created_at' => Carbon::now(),
```