We will create a seeder to populate the `todos` table with some initial data.

Run this command to create a seeder:

```
php artisan make:seeder TodoSeeder
```

This will create a new seeder file in the `database/seeders` directory. Open the generated file in `database/seeders/TodoSeeder.php` and update it:

```
<?php

namespace Database\Seeders;

use Illuminate\Database\Console\Seeds\WithoutModelEvents;
use Illuminate\Database\Seeder;
use Illuminate\Support\Facades\DB;
use Carbon\Carbon;

class TodoSeeder extends Seeder
{
    public function run()
    {
        DB::table('todos')->insert([
            [
                'task' => 'Buy groceries',
                'completed' => false,
                'created_at' => Carbon::now(),
                'updated_at' => Carbon::now()
            ],
            [
                'task' => 'Buy fruits',
                'completed' => false,
                'created_at' => Carbon::now(),
                'updated_at' => Carbon::now()
            ],
            [
                'task' => 'Complete Laravel project',
                'completed' => true,
                'created_at' => Carbon::now(),
                'updated_at' => Carbon::now()
            ],
        ]);
    }
}
```

This code defines a seeder that inserts three dummy tasks into the `todos` table.

Seed the database:

```
php artisan db:seed --class=TodoSeeder
```

Now you can see the `todos` table with dummy data in the MySQL database, `tododb`.

10.6.5.5 Step 5: Create the Todo Model

We will create a model for the `todos` table to interact with it using Eloquent ORM.