This code defines the `tags` table with a unique `name` column. This establishes a **Many-to-Many relationship** between posts and tags. The `name` column is used to store the name of each tag.

Finally, we need to create a pivot table for the **Many-to-Many relationship** between posts and tags. This table will be named `post_tag` and will contain two foreign keys: `post_id` and `tag_id`.

Edit `database/migrations/YYYY_MM_DD_create_post_tag_table.php`:

```
return new class extends Migration {
    public function up()
    {
        Schema::create('post_tag', function (Blueprint $table) {
            $table->id();
            $table->unsignedBigInteger('post_id');
            $table->unsignedBigInteger('tag_id');
            $table->timestamps();

            $table->foreign('post_id')->references('id')->on('posts')->onDelete('cascade');
            $table->foreign('tag_id')->references('id')->on('tags')->onDelete('cascade');
        });
    }

    public function down()
    {
        Schema::dropIfExists('post_tag');
    }
};
```

This code defines the `post_tag` table with two foreign key references: `post_id` and `tag_id`. This establishes a **Many-to-Many relationship** between posts and tags. The `post_id` column is used to associate each tag with a specific post, and the `tag_id` column is used to associate each post with a specific tag.

After editing the migration files, we need to run the migrations to create the tables in the SQLite database. Make sure to run the following command to create the tables in the SQLite database:

```
php artisan migrate
```

You should see a message indicating that the migrations were successful. You can check the SQLite database to confirm that the tables have been created.

If you open the SQLite database file in DBeaver, you should see table relations like this: