10.8.4.4 Step 4: Create a Seeder for Dummy Data

We will create a seeder to populate the `products` table with dummy data. Run the following command:

```
php artisan make:seeder ProductSeeder
```

This command creates a new seeder file in `database/seeders/ProductSeeder.php`. Open the generated file in `database/seeders/ProductSeeder.php` and update it:

```
namespace Database\Seeders;

use Illuminate\Database\Seeder;
use App\Models\Product;

class ProductSeeder extends Seeder
{
    public function run(): void
    {
        Product::factory()->count(50)->create();
    }
}
```

This code defines the `ProductSeeder` class and uses a factory to create 50 dummy products. We will create the factory in the next step.

We modify `Product.php` to use the `HasFactory` trait. Open the generated file in `app/Models/Product.php` and update it:

```
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Model;
use Illuminate\Database\Eloquent\Factories\HasFactory;
class Product extends Model
{
    use HasFactory;

    protected $fillable = ['name', 'price',];
}
```

Next, we need to create a factory for the `Product` model. Run the following command:

```
php artisan make:factory ProductFactory --model=Product
```

This command creates a new factory file in `database/factories/ProductFactory.php`. Open the generated file in `database/factories/ProductFactory.php` and update it:

```
namespace Database\Factories;

use Illuminate\Database\Eloquent\Factories\Factory;

class ProductFactory extends Factory
```