```
// Route::get('/', function () {
//     return view('welcome');
// });
```

save the file. This will set up the route for the report generation.

11.7.4.7 Step 7: Create View with Bootstrap

We will create a view to display the report. Create a new directory named `reports` in the `resources/views` directory. Inside the `reports` directory, create a file named `index.blade.php`.

Codes for `resources/views/reports/index.blade.php`:

```
<!DOCTYPE html>
<html>
<head>
    <title>Order Report</title>
    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
rel="stylesheet">
</head>
<body>
<div class="container mt-5">
    <h2>User Order Summary</h2>
    <table class="table table-bordered">
        <thead>
            <tr>
                <th>User</th>
                <th>Total Orders</th>
                <th>Total Spent ($)</th>
            </tr>
        </thead>
        <tbody>
        @foreach($reports as $report)
            <tr>
                <td>{{ $report->user_name }}</td>
                <td>{{ $report->total_orders }}</td>
                <td>{{ number_format($report->total_spent, 2) }}</td>
            </tr>
        @endforeach
        </tbody>
    </table>
</div>
</body>
</html>
```

Save the file. This view will display the report in a Bootstrap-styled table.

11.7.4.8 Step 8: Run the App

After creating the view, you can run the application using the built-in PHP server:

```
php artisan serve
```