```
use Illuminate\Support\Facades\DB;

public function run(): void
{
    DB::table('employees')->insert([
        ['name' => 'Hiroshi', 'salary' => 5500, 'years_of_service' => 3],
        ['name' => 'Yuki', 'salary' => 7200, 'years_of_service' => 4],
        ['name' => 'Liam', 'salary' => 9500, 'years_of_service' => 6],
        ['name' => 'Emma', 'salary' => 11000, 'years_of_service' => 9],
    ]);
}
```

Save the file. This seeder will insert sample data into the `employees` table.

Modify the `database/seeders/DatabaseSeeder.php` file to call the `EmployeeSeeder`:

```
// In DatabaseSeeder.php
class DatabaseSeeder extends Seeder
{
    public function run(): void
    {
        $this->call(EmployeeSeeder::class);
    }
}
```

Now run the seeder to populate the `employees` table:

```
php artisan db:seed
```

You can verify that the table has been populated by checking the database file or using a database management tool.

11.8.4.5 Step 5: Create Controller

We will create a controller to handle the report generation.

```
php artisan make:controller EmployeeReportController
```

You can find the newly created controller file in the `app/Http/Controllers` directory. Open the newly created file and add the following code to generate the report.

Edit `app/Http/Controllers/EmployeeReportController.php`:

```
namespace App\Http\Controllers;

use Illuminate\Http\Request;
use Illuminate\Support\Facades\DB;

class EmployeeReportController extends Controller
{
    public function index(Request $request)
```