```
    'mongodb' => [
        'driver'   => 'mongodb',
        'dsn' => env('MONGODB_URI', 'mongodb://appuser:pass12345@127.0.0.1:27017/productdb
        'database' => env('MONGODB_DATABASE', 'productdb'),
    ],
```

Set default connection to `mongodb` in the `default` key:

```
'default' => env('DB_CONNECTION', 'mongodb'),
```

This tells Laravel to use the MongoDB connection when interacting with the database.

We need to activate MongoDB provider in the `bootstrap/providers.php` file. Open the `bootstrap/providers.php` file and add the following line to the `MongoDB\Laravel\MongoDBServiceProvider::clas` inside return array:

```
<?php

return [
    ...

    MongoDB\Laravel\MongoDBServiceProvider::class,
];
```

Save all the files and close them.

We need to refresh the configuration cache to apply the changes. Run the following command in your terminal:

```
php artisan config:cache
```

This command will clear the configuration cache and regenerate it with the new settings.

12.10.4.6 Step 6: Create the Product Model

We will create a `Product` model to interact with the `products` collection in MongoDB. Run the following command to create the model:

```
php artisan make:model Product
```

This will create a new file called `Product.php` in the `app/Models` directory. Open the `Product.php` file and update it as follows: