```
knowYourClassicMetal(album: 'Somewhere in Time', artist: 'Iron Maiden',
year: '1985', label: 'EMI', artist: 'Iron Maiden');
```

```
Output:
Fatal error: Uncaught Error: Named parameter $artist overwrites previous
argument
```

Mixing Call Styles

Both named arguments and unpacked arrays can be combined with the traditional positional form, and if you're feeling particularly adventurous, it is even possible (since PHP 8.1) to put named parameters after an unpacked array. Some extra care needs to be taken, however. There are some gotchas.

First of all, positional parameters can only go before named. The following is absolutely fine:

```
knowYourClassicMetal('Painkiller', 'Judas Priest', year: '1990', label:
'Columbia Records');
```

```
Output:
Painkiller by Judas Priest, released in 1990 on Columbia Records
```

But this is not…

```
knowYourClassicMetal(album: 'Painkiller', 'Judas Priest', year: '1990',
label: 'Columbia Records');
```

```
Output:
Fatal error: Cannot use positional argument after named argument
```

Unpacked arguments have the same restriction. It's fine to use multiple unpacked arrays like this: `testArgs(...$strings, ...$moreStrings)`. Otherwise, unpacked arguments must go after positional. Here's what happens if a positional argument is placed after unpacking:

```
$strings = ['I', 'hope', 'this', 'makes', 'sense'];
$moreStrings = 'too';
testArgs(...$strings, $moreStrings);
```