Searching by Callback

PHP 8.4 introduced four new array functions which work by iterating keys and values, and passing them to a callback function. The first two we'll look at are `array_find()` and `array_find_key()`. Both these functions will iterate over the searched array and pass the values (and keys, if required) to the callback function, which should return a `bool` value. On the first `true` callback return, `array_find()` returns the corresponding element value, and `array_find_key()` returns the corresponding key, like so:

```
$guitars = [
    'Suhr',
    'Stratocaster',
    'Stratocaster',
];

$axe = array_find(
    $guitars,
    fn ($val): bool => strlen($val) > 4
);

$index = array_find_key(
    $guitars,
    fn ($val): bool => strlen($val) > 4
);

print "Let's play the {$axe} today." . PHP_EOL;
print "It's the one in position {$index}";

Output:
Let's play the Stratocaster today.
It's the one in position 1
```

Here we've used `array_find()` and `array_find_key()` in conjunction with a simple arrow function, you can also use a standard anonymous function or a string containing the name of a declared function. The signature of the callback is `(mixed $val, mixed $key): bool` – in other words, it must accept `mixed` for element values as the first parameter and `mixed` for element keys as the second (optional) parameter. Our arrow function tests the length of the `$val` string with `strlen() > 4` and returns the boolean