```
php7.4-fpm - server-side, HTML-embedded scripting language (FPM-CGI binary)

$ apt-cache search "php7.3 "
php7.3-cli - command-line interpreter for the PHP scripting language
php7.3-dev - Files for PHP7.3 module development
php7.3-fpm - server-side, HTML-embedded scripting language (FPM-CGI binary)

$ apt-cache search "php8.4 "
php8.4-cli - command-line interpreter for the PHP scripting language
php8.4-dev - Files for PHP8.1 module development
php8.4-fpm - server-side, HTML-embedded scripting language (FPM-CGI binary)
```

Debian users can switch between different versions of PHP if there are multiple installed. Let's first install PHP 7.4 and PHP 8.4:

```
$ sudo apt-get install -y php7.4
Reading package lists... Done
Building dependency tree... Done
...
$ sudo apt-get install -y php8.4
Reading package lists... Done
Building dependency tree... Done
...
```

Now let's see which version we'll get by default:

```
$ php -v
PHP 8.4.11 (cli) (built: Aug  3 2025 08:48:18) (NTS)
```

This should make sense: it's (at time of writing) the latest version and the last thing we installed. What if we want to run PHP 7.4, though? If you've followed the instructions so far, there should be two binaries on your system in addition to `php`: `php7.4` and `php8.4`.

```
$ which php
/usr/bin/php

$ which php7.4
/usr/bin/php7.4
```