Creating New Values With `array_reduce()`

Similar to `array_map()`, PHP's built-in `array_reduce()` allows you to define a callback function, which will execute for every element. Rather than producing a new array of equal size, `array_reduce()` instead accumulates data to be returned once processing is finished. The returned data can be a scalar or compound type. Like `array_map()`, the original array will remain unchanged:

```
$stock = [
    ['brand' => 'VW', 'model' => 'Golf GTI', 'value' => 20000],
    ['brand' => 'VW', 'model' => 'Scirocco GTI', 'value' => 16000],
    ['brand' => 'VW', 'model' => 'Corrado VR6', 'value' => 12000],
    ['brand' => 'Ford', 'model' => 'Escort RS2000', 'value' => 35000],
    ['brand' => 'Ford', 'model' => 'Sierra RS Cosworth', 'value' => 25000],
    ['brand' => 'Peugeot', 'model' => '205 GTI', 'value' => 10000],
];

$stockTally = array_reduce(
    $stock,
    function (array $accumulator, array $element): array {
        $accumulator[$element['brand']] += $element['value'];
        return $accumulator;
    },
    ['VW' => 0, 'Ford' => 0, 'Peugeot' => 0] // unset array keys
                                             now generate Warning
                                             errors in PHP8
);

print_r($stockTally);

Output:
Array
(
    [VW] => 48000
    [Ford] => 60000
    [Peugeot] => 10000
)
```